



Pentair FreshPoint Reverse Osmosis

3, 4, & 5 Stage RO Systems



Item #	Description	GPD
RF-3	3 Stage	50
RF-4	4 Stage	75
RF-4R	4 Stage w/TDS Monitor	75
RF-5	5 Stage	75
RF-5R	5 Stage w/TDS Monitor	75

Leak Detector 68-L38F



Always incorporate appropriate leak protection devices/methods to prevent/mitigate potential water damage



Simple and reliable quick change design. The best on the market!

- ◆ High efficiency GRO 50 and 75 GPD membrane technology
- ◆ Effortless click-in lock cartridge installation
- ◆ 3/8" push fit plumbing connection for easy installation and high flow rated
- ◆ Water supply valve shut off fits multiple piping styles
- ◆ Color coded cartridges to maintain proper filter sequence
- ◆ Lead and chemical reduction cartridge
- ◆ 3/8" tubing to storage tank and faucet
- ◆ Built-in check valve with multi-point backflow protection
- ◆ Utilizes the dual technology of the DFX Diamond Flow series combining a sediment and carbon block in one cartridge
- ◆ High capacity tank and faucet with air gap included
- ◆ Optional On board TDS monitor measures rejection of GRO element on 4 and 5 stage units



Replacement filters

Item #	1 st Stage	2 nd Stage	3 rd Stage	4 th Stage	5 th Stage
3 Stage	62F-655123 Sediment/Carbon	62F-655121 50 GPD "RO" Membrane	62F-655117 Post Filter	X	X
4 Stage	62F-655123 Sediment/Carbon	62F-655122 75 GPD "RO" Membrane	62F-655120 Lead & Chemical	62F-655117 Post Filter	X
5 Stage	62F-655123 Sediment/Carbon	62F-655122 75 GPD "RO" Membrane	62F-655126* Lead & Chemical	62F-655126* Lead & Chemical	62F-655117 Post Filter

*Sold as a Pair





Pentair FreshPoint Filtration

1, 2, & 3 Stage Filter Systems



Item #	Description	Function	Replacement Filters	~ Capacity	NSF
FF1	1 Stage	Color, Taste and Odor	62F-655123	750 Gal.	42
FF1P	1 Stage Plus	Color, Taste, Odor, Lead, Cyst and Chemical	62F-655123	750 Gal.	42/53
FF2	2 Stage	Color, Taste, Odor, Lead, Cyst and Chemical	62F-655126*	675 Gal.	42/53
FF3	3 Stage	Sediment/Color, Taste, Odor,	62F-655116, 62F-655126*	675 Gal	42/53

*Sold as a Pair

- ◆ Effortless click-in lock cartridge installation
- ◆ 3/8" push fit plumbing connection for easy installation and high flow rates
- ◆ Water supply valve shut off fits multiple piping styles
- ◆ Color coded cartridges to maintain proper filter sequence
- ◆ 3/8" tubing for higher flow rates
- ◆ Built-in check valve with multi-point backflow protection
- ◆ High quality faucet included
- ◆ Optional electronic timer indicates when a filter change is needed.



Leak Detector
68-L38F



Simple timer indicated when 12 months have passed ensuring the customer replaces the filters annually.

NSF 42	Average Reduction
Chlorine, Taste and odor	>95.9%
Particulates (0.5-<1uM)	>97.9%

NSF 53	Reduction
Cysts	>99.97%
Altazine	>90.5%
Lead	>99.3%
Lindane	>94.0%
Chloro-form	>96.5%

Always incorporate appropriate leak protection devices/methods to prevent/mitigate potential water

