

i5 1-1/4" Sediment

The i5 series by IWP. Simple maintenance, high performance, and excellent flow rates. Clinoptilolite reduces sediment down to 3-5 microns. Filter-Ag is lightweight and is commonly used as a replacement to Multi-media reducing sediment to the 20-40 micron range. i5 systems include a flow meter and a high flow bypass.



Item #	GAC ft ³	Media Type	Mineral Tank	≈Service/ Peak GPM	≈Backwash Rate GPM
BW-i12M-1054-CLA	1.5	Clinoptilolite	10" x 54"	11/16	9
BW-i12M-1252-CLA	2	Clinoptilolite	12" x 52"	15/17	12
BW-i12M-1354-CLA	2.5	Clinoptilolite	13" x 54"	17/19	15
BW-i12M-1465-CLA	3	Clinoptilolite	14" x 65"	20/20	20
BW-i12M-1665-CLA	4	Clinoptilolite	16" x 65"	20/22	20
BW-i12M-1865-CLA	5	Clinoptilolite	18" x 65"	20/23	25
BW-i12M-1054-FAA	1.5	Filter-Ag	10" x 54"	3+/16	4.5
BW-i12M-1252-FAA	2	Filter-Ag	12" x 52"	4+/17	7
BW-i12M-1354-FAA	2.5	Filter-Ag	13" x 54"	5+/19	8
BW-i12M-1465-FAA	3	Filter-Ag	14" x 65"	5+/20	9
BW-i12M-1665-FAA	4	Filter-Ag	16" x 65"	7+/22	12
BW-i12M-1865-FAA	5	Filter-Ag	18" x 65"	9+/23	15
BW-i12M-2165-FAA	6	Filter-Ag	21" x 62"	12+/24	20

See the "CK Series Parts & Accessories" page for installation parts

